

Material number	0 611 917 080
EAN	4059952600673
Grease tube spare part number 1 615 430 010	✓
Machine cloth	✓
XL-BOXX 1 605 438 1JH	✓



Technical data

Technical data

Impact energy (according to EPTA 05/2016)	9 J
Impact rate at rated speed	0 – 3,130 bpm
Rated speed	0 – 360 rpm
Weight excl. battery	7 kg
Tool holder	SDS max
Tool dimensions (width)	132 mm
Tool dimensions (length)	502 mm
Tool dimensions (height)	253 mm
Battery voltage	18.0 V
Product category subdivision	Cordless Rotary Hammer BITURBO with SDS max
BITURBO	Yes



Drilling range

Hammer drilling diameter range in concrete	12 – 40 mm
Recommended drilling diameter range in concrete	18 – 32 mm

Noise/vibration information

Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 93 dB(A); Sound power level 104 dB(A). Uncertainty K= 4 dB.
-------------	---

Sales information

Positioning

- Cordless freedom with corded performance - SDS-max all-rounder for concrete chiselling and drilling up to 40mm

User benefit

- BITURBO Brushless technology with ProCORE18V for corded performance providing powerful 9.0 J impact energy
- Optimal power-to-weight ratio due to an improved impact mechanism and highly capable drive train
- Minimised hand and arm injuries by instantly shutting down the rotary hammer thanks to KickBack Control

